

TF500S



TF500S

## Specification

- 5.0m (16ft 6in) reach
- Parallel arm geometry
- 1.2m cut DS flailhead (belt drive)
- Totally Independent hydraulics
- 3-point linkage mounted (Cat II)
- Machine weight 1100kg
- 140 litre capacity
- 240° head rotation
- Cast iron pumps and motor
- Cable controls - 45hp motor
- Low pressure hydraulic proportional control joystick option (TF500SLP)- 50hp motor



Cable Controls



Low Pressure Hydraulic Proportional Joystick

## Features

- 100° Power Slew
- Hydraulic safety breakback
- Head Float
- Dual direction flail rotation
- Cab safety guard kit
- Bar stabiliser kit
- Oil included
- Minimum tractor requirement **65hp, 2500kg.**

## Optional Extra for TF Models

- Boom float kit

TP625T



## TP625T

### Specification

- 6.25m (20ft 6in) maximum reach
- Parallel arm geometry
- 1.0m Telescopic Reach
- 1.2m cut DS flailhead (belt drive)
- Totally Independent hydraulics
- 3-point linkage mounted (Cat II)
- Machine weight 1500kg
- 200 litre capacity
- 240° head rotation
- Cast iron pumps and 65hp motor
- Low pressure hydraulic proportional control joystick



Low Pressure  
Hydraulic  
Proportional Joystick

### Features

- 100° Power Slew
- Hydraulic safety breakaway
- Head Float
- Dual direction flail rotation
- Cab safety guard kit
- Bar stabiliser kit
- Oil included
- Road lighting as standard
- Minimum tractor requirement **100hp, 3750kg.**

### Optional Extras for TP Models

- Debris blower
- Boom float kit