

Horizontal Hydraulic Folding Cast Rollers

5 Section


- 10.4m (34') or 12.4m (41') working widths
- Robust fabricated steel frame
- Large wheels and tyres for fast smooth road transport
- Triple sealed bearings
- Simple adjustment of rings with cam adjusters
- Pivoting wing sections allow rolls to follow ground contours
- Transport lock for wing sections
- Ring size options
- One double acting ram to convert from transport to working position
- Double acting ram folds and unfolds each outer section
- Final folding manoeuvre simply achieved by driving forward

Rolling width	10.4m (34')			12.4m (41')		
	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings
Diameter of rings	55cm (22")	55cm (22")	61cm (24")	55cm (22")	55cm (22")	61cm (24")
Product code	UWF/34/C1	UWF/34/CB4	UWF/34/LC2	UWF/41/C1	UWF/41/CB4	UWF/41/LC2
Weight	4668kg	6542kg	6015kg	5566kg	7800kg	7235kg
Transport width	2.9m (9'6")			2.9m (9'6")		
Tyre size	15R 22.5 (Super Singles)			15R 22.5 (Super Singles)		
Bearing and axle diameter	65mm (2.5")			65mm (2.5")		



Castellated Ring Profiles

Castellated rings are unique to Twose and fitted as standard. The castellated ring profile has outstanding clod breaking and tilling characteristics to produce a surface seed bed with good capillary action and maximum crop establishment.



Transport position