

# Horizontal Hydraulic Folding Cast Rollers

## 3 Section - Heavy Duty with Levelling Boards


- 6.4m (21'), 7.3m (24') or 8.2m (27') working widths
- Robust fabricated steel frame
- Large wheels and tyres for fast smooth road transport
- Triple sealed bearings
- Transport wheels are well clear of ground when rolling
- Simple adjustment of rings
- Centre pivot wing sections allow rolls to follow ground contours
- Transport cradle for wing sections
- Ring size options

## Levelling Boards

- Reduces the number of passes to form seed bed
- Adjustable working height and tine angle
- Spring steel tines with adjustable hard steel tips

### Castellated Ring Profiles

Castellated rings are unique to Twose and fitted as standard. The ring profile has outstanding clod breaking and tilling characteristics to produce a surface seed bed with good capillary action and maximum crop establishment.



Rolling width	6.4m (21')			7.3m (24')			8.2m (27')				
Ring type	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings		
Diameter of rings	55cm (22")	55cm (22")	61cm (24")	55cm (22")	55cm (22")	61cm (24")	61cm (24")	55cm (22")	55cm (22")	61cm (24")	
Product code	640C1L	640CB4L	640CB5L	640LC2L	730C1L	730CB4L	730CB5L	730LC2L	820C1L	820CB4L	820LC2L
Weight	4350kg	5000kg	5300kg	4650kg	4650kg	5400kg	5700kg	5050kg	4950kg	5800kg	5450kg
Transport width	2.70m (8'10")			2.70m (8'10")			2.70m (8'10")				
Tyre size	12.5/80 x 15.3 - 14 ply			12.5/80 x 15.3 - 14 ply			12.5/80 x 15.3 - 14 ply				
Bearing and axle diameter	65mm (2.5")			65mm (2.5")			65mm (2.5")				

*All models can be supplied without levelling boards*



Transport position



Levelling boards